

(12) NACH DEM VERTRAG ÜBER DIE INTERNATIONALE ZUSAMMENARBEIT AUF DEM GEBIET DES
PATENTWESENS (PCT) VERÖFFENTLICHTE INTERNATIONALE ANMELDUNG

(19) Weltorganisation für geistiges Eigentum
Internationales Büro



(43) Internationales Veröffentlichungsdatum
15. April 2004 (15.04.2004)

PCT

(10) Internationale Veröffentlichungsnummer
WO 2004/031598 A1

(51) Internationale Patentklassifikation⁷: F16B 21/08,
19/00, 2/22

(21) Internationales Aktenzeichen: PCT/EP2003/010364

(22) Internationales Anmeldedatum:
18. September 2003 (18.09.2003)

(25) Einreichungssprache: Deutsch

(26) Veröffentlichungssprache: Deutsch

(30) Angaben zur Priorität:
102 45 276.8 27. September 2002 (27.09.2002) DE

(71) Anmelder (für alle Bestimmungsstaaten mit Ausnahme von
US): A. RAYMOND & CIE [FR/FR]; 113, Cours Berriat,
F-38028 Grenoble (FR).

(72) Erfinder; und

(75) Erfinder/Anmelder (nur für US): ZOUBEK, Viktor
[CZ/CZ]; Na Vysine 7, 46601 Jablonec nad Nisou (CZ).
SASEK, Vaclav [CZ/CZ]; Melantrichova 6/208, 46006
Liberec (CZ).

(74) Anwalt: RÜTTGERS, Joachim; A. Raymond GmbH &
Co. KG, Teichstr. 57, 79539 Lörrach (DE).

(81) Bestimmungsstaaten (national): AE, AU, BR, CN, JP,
KR, MX, PH, PL, RO, RU, SK, UA, US, ZA.

(84) Bestimmungsstaaten (regional): europäisches Patent (AT,
BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR,
HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).


Veröffentlicht:

— mit internationalem Recherchenbericht

[Fortsetzung auf der nächsten Seite]

(54) Title: FIXING ELEMENT

(54) Bezeichnung: BEFESTIGUNGSELEMENT



(57) Abstract: The invention relates to a fixing element for fixing a component to a support part. Said element comprises a retaining part (1) for the component to be fixed and a hollow anchor foot (2), which is used to anchor the fixing element in a continuous bore of the support part. Two sprung arm pairs (5, 6), which widen towards the retaining part (1), run from the lower edge in opposing openings (4) in the wall of the anchor foot (2), one short and one long sprung arm (5 and 6) respectively lying adjacent to one another in one of the openings (4) and being offset in relation to the short and long sprung arm (5 and 6) in the other opening (4). As both sprung arm pairs (5, 6) are graduated towards the retaining part (1), starting from a respective outer edge (11, 12) that lies at the greatest radial distance from the central axis (M) of the fixing element, front faces (7, 8) and step faces (9, 10) are created on different horizontal planes. Said faces can rest on the underside of a support part. Vertical bearing faces are created simultaneously (13, 14) at different radial distances from the central axis (M). Said vertical faces can rest on the peripheral face of bores of varying diameters. The fixing element can thus be used both for a wide range of material strengths of the support part and for a wide range of diameters of the bore with high functional reliability. Both ranges can be covered by small graduation increments. An umbrella-shaped, sprung stop (15) lying between the retaining part (1) and

the anchor foot (2) permits a continuous adaptation between the stages for the range of material strengths.

[Fortsetzung auf der nächsten Seite]